PRODUCT & APPLICATION GUIDE

CHEMICAL MONITORING & CONTROL

WEIGHING SCALES

LEVEL SENSORS

DILUTION SYSTEMS

FORCE FLOW

CHEMICAL MONITORING & CONTROL

INDICATORS



WIZARD 4000 ADVANCED INDICATOR

SOLO-63
#1 NET 1255, 4 LB

SOLO G2® ELECTRONIC INDICATOR



HYPO TRAK® MONITORING SYSTEM

POWERFUL SOFTWARE ALLOWS YOU TO MONITOR USAGES, FEED RATES AND REMAINING CHEMICALS ON UP TO 4 SEPARATE TANKS. REMOTE MONITORING VIA 4-20MA OR RS232/RS485 AND UP TO 12 RELAYS FOR LEVEL AND RATE ALARMS.

ECONOMICAL AND SIMPLE TO OPERATE, THIS INDICATOR FEATURES EASY KEYPAD NAVIGATION AND DATA ENTRY, A HIGH RESOLUTION DIGITAL DISPLAY AND STANDARD 4-20MA OUTPUTS.

SINGLE OR DUAL CHANNEL MODELS

PERFECT FOR SODIUM HYPOCHLORITE FEED APPLICATIONS. SEE AMOUNT FED, WARN OF VAPOR LOCKED METERING PUMPS, AND MONITORING STRENGTH DEGRADATION.

APPLICATIONS



VOLUMETRIC FEEDER SCALE

PROVIDES LOSS-IN-WEIGHT MEASUREMENT WHEN FEEDING DRY CHEMICALS, SUCH AS POSTASSIUM PERMANGANATE, POWDER ACTIVATED CARBON, DRY POLYMER, DRY FLUORIDE, CALCIUM HYPOCHLORITE AND BISULFITE.

BULLETIN



CHLOR-SCALE® 150

OFFERS AN EASY AND ACCURATE WAY TO MONITOR CHLORINE, SO2, AND AMMONIA CYLINDERS. SOLID PVC PLATFORMS WILL NEVER CORRODE!

BULLETINS 204, 207, 514



CHLOR-SCALE®

SAFE AND RELIABLE WEIGHING SYSTEMS FOR TON CONTAINERS OF CHLORINE AND SO2, MODELS FOR UP TO 6 CONTAINERS.

BULLETINS 202, 203, 401, 402, 408




DRUMM-SCALETM & CARBOY-SCALETM

LOW PROFILE PLATFORM ALLOWS EASY LOADING OF 5 TO 55 GALLON DRUMS. USE WITH HYPOCHLORITE, FLUORIDE, POLYMER AND ORTHOPHOSPHATE DRUMS.

BULLETINS 205, 403, 514, 512, 410

INSTALLATIONS & LOCATIONS



LEVEL

USAGE

FEED RATE



SOLO® XT DIGITAL INDICATOR

CENTURY® HYDRAULIC DIAL INDICATOR



MERLIN® CHEMICAL DILUTION SYSTEM

WHEN LINE VOLTAGE IS UNAVAILABLE, CROSS TECHNOLOGY™ BLENDS THE RUGGED HYDRAULIC LOAD CEL WITH AN EASY TO USE BATTERY OR LOOP POWERED DIGITAL INDICATOR. ALARM RELAY AND 4-20MA OUTPUT OPTIONS.

THE CENTURY DIAL OPERATES HYDRAULICALLY REQUIRING NO POWER. IT IS IMMUNE TO LIGHT-NING, EMI AND RFI AND IS SIMPLE TO INSTALL OPERATE AND MAINTAIN.

AUTOMATED ONSITE DILUTION OF SODIUM HYPOCHLORITE, CAUSTIC, AND OTHER CHEMICALS. ANY STRENGTH AT THE TOUCH OF A BUTTON. DILUTES AS CHEMICAL IS NEEDED OR COMPLETE LOAD AT TIME OF DELIVERY.



PROCELL® LOAD SENSORS

MONITOR BULK STORAGE
TANKS, HOPPERS AND SILOS.
APPLICATIONS INCLUDE
CHLORINE, SULFUR DIOXIDE,
AMMONIA, LIME AND CARBON.

BULLETINS 207, 406



CHEM-SCALE™ & TOTE BIN SCALE

HEAVY-DUTY PLATFORM
DESIGN SAFELY SUPPORTS
AND RESTRAINS TANKS. FOR
DAY TANKS UP TO 500 GALLONS.
FOR DAY TANKS UP TO 500
GALLONS. SODIUM HYPOCHLORITE, FLUORIDE, CAUSTIC, ALUM
AND POLYMER

BULLETINS 206, 404, 411



ULTRASONIC ECHO-SCALE™

PROVIDES CHEMICAL MONITORING ON LARGE TANKS THAT DON'T FIT ON A SCALE PLATFORM. USE STAND-ALONE OR COMBINE WITH OUR WIZARD® OR SOLO® INDICATORS.

BULLETIN 510

TREATED WATER




DOCUMENT YOUR CHEMICAL INVENTORY AND USAGE

SATISFY GOVERNMENT RECORD KEEPING REQUIREMENTS



WARN OF DANGEROUS HIGH FEED, LOW FEED AND NO FEED CONDITIONS

REDUCE OPERATOR EXPOSURE TO CHEMICALS WITH REMOTE MONITORING



ALTERNATIVE CHLORINATION



NEVER RUN OUT OF CHEMICAL AGAIN

ACCURATELY ANTICIPATE CHEMICAL RE-ORDER POINTS

SYSTEM COMPATIBILITY GUIDE





2430 STANWELL DRIVE CONCORD, CA 94520 U.S.A. 925.686.6700 FAX 925.686.6713 EMAIL: INFO@FORCEFLOW.COM



COMMITTED TO CUSTOMER SERVICE AND PRODUCT SUPPORT

FROM THE INITIAL WRITING
OF A SPECIFICATION THROUGH
THE INSTALLATION AND
OPERATION OF THE EQUIPMENT,
100% SATISFACTION IS OUR
GOAL. AT FORCE FLOW, WE KNOW
THAT A SUPERIOR CUSTOMER
SERVICE AND SUPPORT TEAM IS
CRUCIAL TO THE SUCCESS OF
OUR COMPANY

SERVICE

OUR POLICY IS TO GET ALL REPAIRS, WARRANTY WORK AND RETROFITS COMPLETED AND SHIPPED WITHIN 48 HOURS OF THEIR ARRIVAL AT THE FACTORY. TRAINED TECHNICIANS AND A LARGE PARTS INVENTORY MAKE THIS HAPPEN. WE UNDERSTAND THAT THERE IS NOTHING MORE FRUSTRATING THAN SENDING SOMETHING BACK TO THE MANUFACTURER AND WONDERING WHEN YOU WILL SEE IT AGAIN. TWO DAY TURNAROUND--THAT IS OUR POLICY! FOR PROMPT SERVICE, CALL OUR TOLL FREE HELP HOTLINE AT (800) 893-6723.

TECHNICAL & APPLICATION SUPPORT

FORCE FLOW FACTORY
ENGINEERS HAVE STRONG
TECHNICAL BACKGROUNDS
WITH MANY YEARS OF PROCESS
WEIGHING EXPERIENCE IN BOTH
CHLORINE AND CHEMICAL FEED
APPLICATIONS. IF YOU REQUIRE
TECHNICAL INFORMATION,
APPLICATION SUPPORT OR HELP
WITH A CUSTOM PROJECT,
PLEASE CONTACT AN
APPLICATION ENGINEER ON OUR
HELP HOTLINE (800) 893 6723

